

Specifications type KB 3..

Single-stage (side channel blowers)

- NSK bearings with high temperature grease
- CE, UL and CSA approved
- All units are QC inspected by Klee
- Built-in bi-metal switch for 1-phase models
- Available with 3-phase IE2/IE3 motor



Type no.		KB-329	KB-329-1	KB-329L	KB-329L-1	KB-329	KB-339
Phases		3	1	3	1	3	3
Output kW	50 Hz	0.75	0.75	0.75	0.75	0.9	1.3
	60 Hz	0.85	0.85	0.85	0.85	1.1	1.5
Voltage Volt	50 Hz	230/400	230	230/400	230	230/400	230/400
	60 Hz	276/480	230	276/480	230	276/480	276/480
Current Amp	50 Hz	3.3/1.9	6.5	3.3/1.9	6.5	4.2/2.4	4.6/2.7
	60 Hz	3.6/2.1	7	3.6/2.1	7	4.5/2.6	5.2/3.0
Vacuum mbar	50 Hz	140	140	140	140	165	175
	60 Hz	140	140	140	140	180	205
Pressure mbar	50 Hz	140	140	140	140	180	200
	60 Hz	140	140	140	140	180	230
Airflow m³/min	50 Hz	2.4	2.4	2.4	2.4	2.4	2.4
	60 Hz	2.9	2.9	2.9	2.9	2.9	2.9
Insulation class		F	F	F	F	F	F
L1		129	129	161	161	129	129
L2		279	279	311.5	311.5	279	279
Weight Kg		14.5	15	15.5	15	15.5	16

